

BENZEX

DIGITAL TERRESTRIAL RECEIVERS

MTR 9500



Features:

- MPEG-2 digital & fully DVB-T compliant
- Automatic PAL/NTSC conversion
- 1000 channels TV and Radio programmable
- 8 different favorite groups selection
- On screen display with OSD multi-language
- Fully support to 7 days Electronic Program Guide(EPG)
- Picture in Graphics(PIG) support
- 256 colors On Screen Display
- Channel search auto scan, manual scan
- Various channel editing
- Function(favorite, move, lock, skip, delete, rename, find, sort)
- Parental control for channels
- Easy installation, with an ease to use Menu System



USB Universal Serial Bus
Personal Video Recorder
PVR



SPECIFICATION

HIGH FREQUENCY

Input Frequency Range	: 170~230MHz, 470~878MHz
VHF&UHF	
IF Bandwidth	: 6、 7 or 8MHz
Input Signal Level	: -72~-20dBm
RF Input Connector	: IEC Type (female)
Input impedance	: 75Ω

DE-MODULE MODE

Modulation mode	: COFDM (Code Orthogonal Frequency Division Multiplexing)
Demodulation	: QPSK, QAM16, QAM64
Mode	: 2K, 8K
Guard interval	: 1/4, 1/8, 1/16, 1/32
Code rate	: 1/2, 2/3, 3/4, 5/6, 7/8

VIDEO, AUDIO

Video decode	: ISO/IEC13818-2 MPEG2 (MP@ML) Compatible
Video resolution	: 720 x 576(PAL); 720 x 480(NTSC)
Video code rate	: 15Mbit/s Max.
Teletext	: support DVB-ETS300472
Audio decode	: ISO/IEC13818-3
Audio Sampling rate	: 32, 44.1, 48KHz

POWER, APPROVAL

Power Input	: 5V
Power consumption	: 5W MAX
Sleep Power consumption	: 1.5W
Approval	: CE
PROCESSOR	: CPU: Ali 3101C1A

UNIT

LED power indicator
IR receiver
RF Input: IEC-type, Female
one Scart

PACKING

Net /Gross Weight: 0.185/0.35 Kgs (single unit)
Unit Dimension : 100 (L) × 66(W) × 23 (H) mm -----NO.A/B case
8-in-1 Export size: TBA
Loading quantity : 20'ft / 40'ft / 40'HQ

ACCESSORIES

User manual: 1pcs
Remote Control: 1pcs
AC-DC adapter: 1pcs
IR extend cable: 1pcs
Batteries: 2pcs AAA battery
USB Cable: 1pcs